Manuelle Spanner

Für Stahlband

Signode Hand Spanner sind leicht zu bedienen und erzielen hohe Bandspannung mit wenig Kraftaufwand. Die meisten Umreifungen werden auf glatten Packstückoberflächen gemacht. Für runde und unregelmäßige Packstücke wird der Einsatz eines Push Type Spanners mit P-Hülse empfohlen.

Spannrad für den allgemeinen Einsatz

Spannradspanner haben ein strukturiertes Spannrad das beim Spannen in die Bandoberfläche eingreift und so das Band zieht. Durch den Spannhebel wird die aufgebrachte Kraft an das Band gebracht und Spannung aufgebaut. Einfach zu bedienen. Gewachste Bänder sind erforderlich.



Model	Artikel Number	Bandabmessung Breite inch	Breite mm	Dicke inch	Dicke mm	Band Type	Band Oberfläche		Gewicht lbs	Gewicht Kg
Spannradspanner										
ST	003480	3/8-3/4	9.5-19.0	0.017-0.023	0.43-0.58				4	1.8
T	003450	5/8-3/4	15.9-19.0	0.017-0.035	0.43-0.64	Apex Plus, Magnus	lackiert & gewachst		5	2.3
TH-34-114	020500	3/4-1-1/4	31.8	0,029-0.035	0.74-0.89	Magnus			7	3.2

Push-type für Rundumreifung



Push-type Spannrad Spanner

PF	017900	3/8-3/4	9.5-19.0	0.017-0.023	0.43-0.58	Apex Plus, Magnus	lackiert & gewachst		4	1.8
PFH	017930	3/4-1-1/4	19.0-31.8	0,025-0.035	G.64-0.89	Apex Plus,	lackiert &		7	3.2

Spezialspanner für besonders hohe Bandspannung

Spezialspanner arbeiten ohne Spannrad. Dafür wird entweder eine geschlitzte Welle oder eine Zahnstange eingesetzt.

Wellen Spanner

4A1-114	184125	1-1/4	31.8	0.029-0.050	0.74-1.27	Magnus	lackiert & gewachst		12	5.4
4A1-2	184140	2	50.8	0.044-0.050	1.12-1.27	Magnus			16	7.3
Zahnstangen Spanner										
PH-2	010065	3/4-1-1/4	19.0-31.8	0.017-0.035	0.43-0.89	Apex Plus, Magnus	lackiert & gewachst		7	3.2

Rack-and-pinion—for heavy round or irregular applications

The rack-and-pinion tensioner uses a serrated gripping dog to hold the pulled strap end. It can be used with either dry or lubricated strapping on round or irregular shaped packages. This tensioner has limited take-up.

1-800-323-2464